FLOWSERVE

Valtek® FlowTop V750 / V752
General Service Control Valve

Get outstanding operating efficiency and performance with maximum versatility



Experience In Motion

Optimized, configurable design provides maximum efficiency and versatility

Flowserve has improved the design of the Valtek FlowTop control valve to meet global requirements for general service and moderately severe service applications.

Building on the proven FlowTop V738/740 and Valtek GS control valve designs, the new Valtek FlowTop valve provides one standardized, versatile control valve with precision control and a variety of trim and packing options to meet a broad range of requirements. The new FlowTop valve offers the same performance and options in an optimized product that's extremely easy to size, select, configure and order.

The fully integrated automated package is available globally and includes an in-line globe style body with a FlowAct pneumatic diaphragm actuator and digital positioner.

Furthermore, the new FlowTop valve design simplifies maintenance and enables cost savings through parts interchangeability.



Proven quality and best-in-class general service performance

- Fully integrated package solution
- Globally available
- Easy to size and select
- High flow rates with excellent rangeability and repeatability
- Quick installation; simple setup
- Severe Service options to minimize noise and cavitation
- Packing options capable of meeting ISO 15848-1, Class BH
- Global support for service and repair
- Severe Service applications

The performance you need with the versatility and ease of maintenance you want


High-performance design — A fully integrated package that features an updated streamlined design for maximum performance and operating efficiency in all general service applications.

Easy to configure and globally available — The updated design is easy to select, size, configure and order. The new FlowTop valve is available globally with numerous options to meet most general service requirements.


Ease of maintenance — A standardized design with interchangeable components simplifies maintenance and minimizes costs related to inventory and spare parts.

Reduced environmental impact — Packing options meet stringent fugitive emissions requirements (ISO 15848-1).

Broad application versatility — Multiple seat designs (threaded or clamped), packing options (external or internal live loaded) and severe service trim solutions for cavitation and noise reduction are available.



Versatile configurations



Specifications an

Style	Globe, angle, integral flange, ASME B16.34 and EN 1349
Sizes	NPS ½ to 12
Pressure classes	Class 150 and 300
Temperature range	Operating temperature: -196°C to 537°C (-320°F to 1000°F) [depending on material and design] Ambient temperature: -40°C to 80°C (-40°F to 176°F) [FlowAct temperature range]
End connection	Flanged, raised face (RF)
Body materials	ISO 15848-1 Class A, B or C for CC1, CC2 or CC3 from -196°C to 600°C
Face-to-face	ISA 75.08.01
Packing	Internal or external, PTFE or graphite, live or non-live loaded, ISO 15848-1, or vacuum
Bonnet	Standard, extended, bellows seal or cryogenic bonnet
Trim material	316 SS, 316L SS, 416 SS HT, 420 SS HT, WC9, 1.4122, 1.4922, Monel 400, Monel K500, Alloy 6 overlay on 316/316L, or Nitrided 316/316L
Low noise and anti-cavitation	MegaStream™ one & two stages, CavStream™ one-stage, CavControl™, and DiamondBack™
Leakage rates	Class IV, V and VI with optional soft seat
Actuator	Pneumatic diaphragm spring actuator
Standard positioner	Digital positioner; also available as integrally mounted to yoke for fail-close/air-to-open configuration; no tubing or bracket required

Flowserve Corporation
5215 North O'Connor Blvd.
Suite 700
Irving, Texas 75039-5421 USA

Flowserve Corporation has established industry leadership in the design and manufacture of its products. When properly selected, this Flowserve product is designed to perform its intended function safely during its useful life. However, the purchaser or user of Flowserve products should be aware that Flowserve products might be used in numerous applications under a wide variety of industrial service conditions. Although Flowserve can provide general guidelines, it cannot provide specific data and warnings for all possible applications. The purchaser/user must therefore assume the ultimate responsibility for the proper sizing and selection, installation, operation, and maintenance of Flowserve products. The purchaser/user should read and understand the Installation Instructions included with the product, and train its employees and contractors in the safe use of Flowserve products in connection with the specific application.

While the information and specifications contained in this literature are believed to be accurate, they are supplied for informative purposes only and should not be considered certified or as a guarantee of satisfactory results by reliance thereon. Nothing contained herein is to be construed as a warranty or guarantee, express or implied, regarding any matter with respect to this product. Because Flowserve is continually improving and upgrading its product design, the specifications, dimensions and information contained herein are subject to change without notice. Should any question arise concerning these provisions, the purchaser/user should contact Flowserve Corporation at any one of its worldwide operations or offices.

©2025 Flowserve Corporation. All rights reserved. This document contains registered and unregistered trademarks of Flowserve Corporation. Other company, product, or service names may be trademarks or service marks of their respective companies.

VAFLY000326-02 (EN/A4) April 2025