



Logix™ 3800e Digital Positioner

Precision valve control optimizes flow rates
and reduces operating costs



Experience In Motion



Logix 3800e digital positioner

Cost-competitive, highly reliable performance and one-button calibration

The Flowserve Logix 3800e positioner is a value-based, robust digital positioner engineered for unmatched performance for valve control and monitoring in oil and gas, petrochemical, and pulp and paper applications. Built on the same platform as the proven design of the Logix 3800 digital positioner from Flowserve, the Logix 3800e positioner is a cost-competitive, easy-to-use, high-precision unit that facilitates improvements in process uptime and yield at low costs.

Installation is simplified with easy configuration and calibration. The Logix 3800e positioner features a one-button setup, which automatically configures the zero, span and gain of the positioner for most valves in less than 60 seconds.

In addition, the Logix 3800e positioner supports a wide variety of double- or single-acting linear and rotary applications. It is compatible with Flowserve linear and rotary valves and actuators and enables easy retrofit to other manufacturers' control valve packages.

Robust and reliable

Trouble-free performance in demanding conditions is ensured by robust housings and a rugged, modular design that provides protection from dirt and water ingress (IP-66), impact and vibration.

Easy configuration and calibration

Innovative quick-calibration feature greatly simplifies commissioning. One-button setup automatically configures the zero, span and gain of the positioner for most valves in less than 60 seconds.

Application versatility

Broad application versatility and well-suited for use with flow-top valves and when explosion-proof design is required; compatible with industry-leading communication technologies, including HART, 4-20 mA or discrete I/O signals. Compatible with a variety of valve and actuation configurations, including any 24V-solenoid valve suitable for the application.

Asset health monitoring (condition monitoring)

The Logix 3800e positioner can be connected to the Flowserve Intelligent Performance Systems (IPS) suite of products, software and services to collect critical process data. Plant operators are empowered to make data-driven decisions and implement preventive actions that can increase equipment availability and minimize unplanned downtime.

Simplified upgrades

The Logix 3800e positioner is identical in form and fit to the Logix 3800 digital positioner, enabling easier upgrades from the Logix 3800e positioner to the Logix 3800 positioner when more analytics are needed.

Low procurement and operational costs

Cost-competitive, high-performance digital positioner designed for high reliability and performance.

Predictive diagnostics

The Logix 3800e positioner has a simplified diagnostic set compared to the Logix 3800 positioner for logging and pinpointing problems in the valve assembly.

The Logix 3800e digital positioner shares the rugged design of the proven Logix 3800 positioner along with its industry-leading levels of quality, simplicity and reliability.

To meet the needs for a cost-competitive alternative, Flowserve developed the Logix 3800e positioner with fewer diagnostic capabilities. For applications requiring a full range of diagnostics, specify the Logix 3800 positioner.

Multiple housing options for improved safety and economy

Explosion-proof or an intrinsically safe housing from -40°C to 85°C (-40°F to 185°F) ensures safe, reliable operation in hazardous conditions. Certified for use in explosion-proof Exd IIC hazardous locations. An economic housing is available with a plastic cover for general purpose applications.



Logix 3800e positioner with intrinsically safe housing with aluminium cover



Logix 3800e digital positioner in explosion-proof housing



Specifications and certifications

Performance characteristics	Description
Air capacity	30.6 Nm ³ /h @ 4.1 bar (18 SCFM @ 60 psi)
Temperature range	-40°C to 85°C (-40°F to 185°F)
Linearity	+/-1.25%
Hysteresis	≤ 1.0%
Sensitivity	≤ 0.25%
Stability	≤ 0.4%
Certifications	Description
Safety	ATEX, IECEx and FM/CSA explosion-proof, intrinsically safe, non-incendive, SIL 3 capable
Communications	HART 6 and 7, 4-20 mA

Flowserve Corporation
5215 North O'Connor Blvd.
Suite 2300
Irving, Texas 75039-5421 USA
Telephone: +1 937-890-5839

Flowserve Corporation has established industry leadership in the design and manufacture of its products. When properly selected, this Flowserve product is designed to perform its intended function safely during its useful life. However, the purchaser or user of Flowserve products should be aware that Flowserve products might be used in numerous applications under a wide variety of industrial service conditions. Although Flowserve can provide general guidelines, it cannot provide specific data and warnings for all possible applications. The purchaser/user must therefore assume the ultimate responsibility for the proper sizing and selection, installation, operation, and maintenance of Flowserve products. The purchaser/user should read and understand the Installation Instructions included with the product, and train its employees and contractors in the safe use of Flowserve products in connection with the specific application.

While the information and specifications contained in this literature are believed to be accurate, they are supplied for informative purposes only and should not be considered certified or as a guarantee of satisfactory results by reliance thereon. Nothing contained herein is to be construed as a warranty or guarantee, express or implied, regarding any matter with respect to this product. Because Flowserve is continually improving and upgrading its product design, the specifications, dimensions and information contained herein are subject to change without notice. Should any question arise concerning these provisions, the purchaser/user should contact Flowserve Corporation at any one of its worldwide operations or offices.

©2021 Flowserve Corporation. All rights reserved. This document contains registered and unregistered trademarks of Flowserve Corporation. Other company, product or service names may be trademarks or service marks of their respective companies.

AIFLY000278 (EN/AQ) February 2021