



HPX-Mag Magnetic Drive Process Pump

Balancing sustainability, reliability and efficiency

The HPX-Mag sealless pump from Flowserve sets a new industry benchmark for magnetic drive pump performance, efficiency and value. It fully complies with API 685 standards and provides a zero-emissions solution for environmentally critical applications.

The HPX-Mag pump represents the most comprehensive range of hydraulic coverage available to the industry, so users can select the correct pump to meet their efficiency desires and application needs.



Typical applications

- Petroleum production, distribution and refining
- Petrochemical and chemical processing
- Difficult-to-seal liquids
- Toxic, aggressive or flammable liquids
- High-temperature applications
- Gas industry services
- Biofuels
- Boiler circulation
- Power plants
- General industrial

Operating parameters

- Rated flows to 1000 m³/h (4400 gpm)
- Heads to 300 m (985 ft)
- Standard pressures to 42 bar (600 psi)*
- Temperatures from -29°C to 300°C (-20°F to 570°F)*

* Higher pressures or temperatures on request



Features and benefits

Leakage-free containment shell made from alloy C4 material delivers high-efficiency performance and high corrosion resistance. The robust construction meets or exceeds API 685 requirements, ensuring zero emissions in difficult-to-seal, toxic, aggressive and flammable liquids.

Hermetically sealed internal flushing system cools the magnet area and lubricates the sleeve bearings, eliminating the need for mechanical seals and external flushing systems.

Dynamic thrust balancing system eliminates the need for mechanical thrust bearings and increases pump reliability, longevity and efficiency while reducing operating costs.

Back pullout design simplifies maintenance activities, as neither the motor nor the piping is disturbed.

High-torque magnets made of rare earth samarium-cobalt eliminate slippage and enable high-temperature resistance.

Centerline-supported pump casing withstands nozzle loads beyond API 685 design requirements. The suction nozzle guide vane reduces inlet vortexing and ensures uniform flow into the impeller to achieve a reliable NPSH margin.

Precision cast impeller is dynamically balanced to limit vibration and assure smooth operation over a wide flow range. The impeller is secured by a set screw and a locknut, which are not exposed to the fluid.

Renewable casing and impeller wear rings, which are secured by set screws or tack welds, reduce replacement parts costs.

World Headquarters

Flowserve Corporation
5215 North O'Connor Blvd.
Suite 2300
Irving, Texas 75039-5421 USA
Telephone: +1 937 890 5839

USA and Canada

Flowserve Corporation
Scienco Pumps
3732 Cook Blvd.
Suite 101
Chesapeake, Virginia 22323 USA
Telephone: 1 800 343 PUMP (7867)

Flowserve Corporation has established industry leadership in the design and manufacture of its products. When properly selected, this Flowserve product is designed to perform its intended function safely during its useful life. However, the purchaser or user of Flowserve products should be aware that Flowserve products might be used in numerous applications under a wide variety of industrial service conditions. Although Flowserve can provide general guidelines, it cannot provide specific data and warnings for all possible applications. The purchaser/user must therefore assume the ultimate responsibility for the proper sizing and selection, installation, operation, and maintenance of Flowserve products. The purchaser/user should read and understand the Installation Instructions included with the product, and train its employees and contractors in the safe use of Flowserve products in connection with the specific application.

While the information and specifications contained in this literature are believed to be accurate, they are supplied for informative purposes only and should not be considered certified or as a guarantee of satisfactory results by reliance thereon. Nothing contained herein is to be construed as a warranty or guarantee, express or implied, regarding any matter with respect to this product. Because Flowserve is continually improving and upgrading its product design, the specifications, dimensions and information contained herein are subject to change without notice. Should any question arise concerning these provisions, the purchaser/user should contact Flowserve Corporation at any one of its worldwide operations or offices.

©2019 Flowserve Corporation. All rights reserved. This document contains registered and unregistered trademarks of Flowserve Corporation. Other company, product, or service names may be trademarks or service marks of their respective companies.

PUFLY000075 (EN/AQ) October 2019