



Smooth, efficient handling of viscous liquids

GR Series between bearings, herringbone gear pumps have long been workhorses within a multitude of industrial markets due to their dependability, efficiency and low total lifecycle cost. GR Series pumps provide high-efficiency, pulse-free pumping, even under the most challenging conditions. They are designed to handle viscous fluids across a broad spectrum of flows and pressures.

GR Series pumps are available in two basic gear widths and with multiple options. With a modular design, GR Series pumps can be customized to satisfy a wide range of applications.

Applications

- Oil circulation
- Process industries
- OEM
- Filtration equipment
- Fire foam systems
- Petrochemical blending and transfer
- Food and beverage processing
- Asphalt and tars
- Grease

Features and benefits

Two-piece doweled construction on each side of the body ensures accurate alignment and facilitates maintenance by allowing faster access to pump internals without disturbing piping.

Full hydraulic balance due to herringbone gears with dual stuffing boxes eliminates the need for specialized balancing devices or thrust bearings.

Between bearings gear design minimizes shaft deflection and reduces bearing loads. High-pressure and high-speed capabilities are improved, extending pump life, improving reliability and lowering total lifecycle costs.

Convertible stuffing box allows for greater flexibility in the use of packing or mechanical seals.

Large, unobstructed suction and discharge passages keep entrance losses and turbulence to a minimum.

High-capacity, double-row roller bearings are standard for long life.


Carbon sleeve bushings may be used when handling liquids with poor lubricity or low viscosities. Also available in antimony-impregnated carbon for high-temperature applications.

Shafts are fine-grain, hot rolled medium carbon steel and generously sized to minimize deflection.

Operating parameters

- Flows to 275 m³/h (1,200 gpm)
- Pressures to 35 bar (500 psi)
- Temperatures to 350°C (650°F)
- Viscosities to 33,000 cps (1 million ssu)
- Speeds to 1,800 rpm
- Standard sizes from 40 to 200 mm (1.5 to 8 in)

GR Series quick selection chart*



* Refer to the above chart for quick selection of the GR pump model corresponding to the desired flow rate. The ranges shown are based on typical viscosities and speeds and assume zero differential pressure. The chart's purpose is to direct the user to the appropriate performance curve, not to be a substitute for it.

**Available upon request.

Materials of construction

Component	Cast Iron Model	Cast Steel Model
Body, Stuffing Box, Bearing Cover, Gland, Sideplates	ASTM A278, Class 35 Cast Iron (Typical)	ASTM A216, Cast Steel Grade WCB
Gears	Cast Iron	Cast Iron
Shaft	ASTM A576, Class 1040 Carbon Steel	
Packing	Graphited Filament Yarn	

Available options

- Inboard bearing with mechanical seal for V-belt drive
- Jacketed pump body
- Integral safety relief valve (up to 3GR size)
- Mechanical seals (various materials available)
- Jacketed stuffing box
- Dual stuffing boxes with packing or mechanical seals
- INSUROCK[®] low-friction wearplates

Flowserve Corporation
 5215 North O'Connor Blvd.
 Suite 2300
 Irving, Texas 75039-5421 USA
 Telephone: +1 937 890 5839

Flowserve Corporation has established industry leadership in the design and manufacture of its products. When properly selected, this Flowserve product is designed to perform its intended function safely during its useful life. However, the purchaser or user of Flowserve products should be aware that Flowserve products might be used in numerous applications under a wide variety of industrial service conditions. Although Flowserve can provide general guidelines, it cannot provide specific data and warnings for all possible applications. The purchaser/user must therefore assume the ultimate responsibility for the proper sizing and selection, installation, operation, and maintenance of Flowserve products. The purchaser/user should read and understand the Installation Instructions included with the product, and train its employees and contractors in the safe use of Flowserve products in connection with the specific application.

While the information and specifications contained in this literature are believed to be accurate, they are supplied for informative purposes only and should not be considered certified or as a guarantee of satisfactory results by reliance thereon. Nothing contained herein is to be construed as a warranty or guarantee, express or implied, regarding any matter with respect to this product. Because Flowserve is continually improving and upgrading its product design, the specifications, dimensions and information contained herein are subject to change without notice. Should any question arise concerning these provisions, the purchaser/user should contact Flowserve Corporation at any one of its worldwide operations or offices.

©2021 Flowserve Corporation. All rights reserved. This document contains registered and unregistered trademarks of Flowserve Corporation. Other company, product, or service names may be trademarks or service marks of their respective companies.

PUFLY000270-01 (EN/A4) April 2021